

Solid State Coaxial Limiters

Communications & Power Industries Solid State Coaxial Limiters



FEATURES:

- Available in UHF, L, S, C, X, Ku and Ka-Bands
- Low loss
- Small size

BENEFITS:

- Long life
- Added functionality and capability
 - Attenuation
 - ENR sources

APPLICATIONS:

- Specification variations available for various market uses

With a history of producing high quality products, we can help you with your coaxial limiters. Contact us at BMDMarketing@cpii.com or at call us at +1 978-922-6000.

Typical Operating Parameters

Frequency	UHF	L-Band	S- Band	C- Band	X- Band	Ku-Band	Ka-Band
Peak Power Handling	5 kW	13 kW	5 kW	200 kW	100 W	50 W	50 W
Average Power Handling	300 W	300 W	500 kW	20 W	10 W	5 W	5 W
Pulse Width	100 ms	100 ms	100 ms	100 ms	50 ms	50 ms	20 ms
Insertion Loss	0.4 dB	0.4 dB	0.8 dB	1.0 dB	1.3 dB	1.5 dB	2.0 dB
Flat Leakage	35 mW	35 mW	35 mW	30 mW	30 mW	30 mW	30 mW
Spike Leakage	150 mW	150 mW	150 mW	100 mW	100 mW	100 mW	100 mW
Recovery Time	5 ms	5 ms	5 ms	5 ms	1 ms	1 ms	1 ms



Beverly Microwave Division
150 Sohler Road
Beverly, Massachusetts
USA 01915

tel +1 978-922-6000
email BMDMarketing@cpii.com
fax +1 978-922-8914
web www.cpii.com

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

©2020 Communications & Power Industries LLC. Company proprietary; use and reproduction is strictly prohibited without written authorization from CPI. 6/20